

CCT10/CCT20



► Features

- Function keys : CCT10 with Numeric 0~9, Count Alarm, Units, Sample, Count, MR, MC, CE, 10 x Piece Weight Memory, Zero, Tare, On, Off
- CCT20 with Numeric 0~9, Count Alarm, Units, Sample, Count, MR, MC, CE, 20 x Piece Weight Memory, Zero, Tare, On, Off
- Power On Zero-Tracking, Auto-Calibration, Auto-Power Off, Digital Noise Filter, Piece Weight Auto-Average, Full Tare, Accumulation Memory, Programmable Capacity and Division, Low Battery Indicator and Charging Status Indicator
- LCD display with LED Backlight, Rechargeable Battery, Power Adaptor, Bubble Level, Stainless Steel Platter, Adjustable Feet and Dust Cover Included
- CCT10 with three LCD displays for Weight, Piece Weight and Total Count, 10 x One-touch Piece Weight Memory keys (Total 20 Piece Weight Memory)
- CCT20 with one large LCD display for Weight, Piece Weight and Total Count, 20 x One-touch Piece Weight Memory keys (Total 40 Piece Weight Memory)

► Specifications

Model	Capacity x Division	Model	Capacity x Division
CCT10-3	3kg x 0.1g	CCT20-3	3kg x 0.1g
CCT10-6	6kg x 0.2g	CCT20-6	6kg x 0.2g
CCT10-15	15kg x 0.5g	CCT20-15	15kg x 0.5g
CCT10-30	30kg x 1g	CCT20-30	30kg x 1g
Power Source:	Rechargeable battery 6V/4Ah or Input DC 100V~240V switching power		
Operating Environment:	-10 °C to 40°C (14°F to 104°F)		
Platter Size:	Stainless Steel 220 x 310mm		

► Options

RS232 output