



### ► Features

- Function keys : CWT7 with Tare x 2, Units, Net/Gross, Print, Zero, On, Off  
CWT22 with Numeric 0-9, Sample, Count, Backlight, M+, Recall, MC, Hi, Lo, I/O set, Print, CE, PT, Units, Net/Gross, Zero, Tare, On, Off
- Straight Weighing Function, Counting Function, Check Weighing HI-OK-LO Function, Multiple Weighing Units Available
- Power On Zero-Tracking, Auto-Calibration, Auto-Power Off mode, Digital Noise Filter, Full Tare, Accumulation Memory, Programmable Capacity and Division, Low Battery Indicator and Charging Status Indicator

### ► Specifications

Model	Capacity x Division	Model	Capacity x Division
CWT7-3	3kg x 0.1g	CWT22-3	3kg x 0.1g
CWT7-6	6kg x 0.2g	CWT22-6	6kg x 0.2g
CWT7-15	15kg x 0.5g	CWT22-15	15kg x 0.5g
CWT7-30	30kg x 1g	CWT22-30	30kg x 1g
Power Source:	Rechargeable battery 6V/4Ah or Input DC 100V~240V switching power		
Operating Environment:	-10 °C to 40°C (14°F to 104°F)		
Platter Size:	Stainless Steel 220 x 310mm		

### ► Options

RS232 output

---