



EWA---LCD display weighing indicator

Features

- ◆AC/DC power supply , A built-in resistance to electromagnetic interference;
- ◆With undervoltage directives and protection device;
- ◆Special software technology, enhance the system's ability to resist vibration.

Standard Functions

- ◆High precision A/D conversion, readability 1/30000/60000;
- ◆With exact counting functions; Can realize manual cumulative function;
- ◆Power-off protection function in weight; With timing shutdown function;
- ◆Alternative and various backlight models;
- ◆Manual revision G value function all over the world;
- ◆With kg/T/G/lb/oz/viss/gangjin/taijin one key conversion function;
- ◆With multiple peaks, maintain stable value function;
- ◆With external calibration convenient functions; Achieve six sections of nonlinear correction.

Specifications

- ◆Accuracy: III
- ◆A/D conversion way: $\Sigma - \Delta$ transformation way
- ◆A/D conversion rate: 30 times/SEC (optional)
- ◆Maximum number of A/D conversion: 20 bit
- ◆Input signal range: - 10 mV~ 15 mV
- ◆Input sensitivity: $\geq 0.1\mu\text{V/d}$
- ◆Working temperature: - 10 ° C to 40 ° C
- ◆Dc power supply: built-in battery 6 V /4 AH (lead)
- ◆The ac power: AC100V - 240 V charger
- ◆Product size: 220 mm (length) * 180mm (wide) * 85 mm (high)
- ◆Sensors for C5V bridge power.

Option
RS232 output

Carbon steelp platform			Stainless steelp platform		
Stainless or carbon steel platter			Stainless steel platter		
Model	Size(mm)	Cap.(kg)	Model	Size(mm)	Cap.(kg)
EWC2828	280*280	3-30	EWS2828	280*280	3-30
EWC3030	300*300	15-150	EWS3030	300*300	15-150
EWC3040	300*400	30-150	EWS3040	300*400	30-150
EWC4040	400*400	30-150	EWS4040	400*400	30-150
EWC4050	400*500	30-300	EWS4050	400*500	30-300
EWC4252	420*520	60-300	EWS4252	420*520	60-300
EWC5060	500*600	60-600	EWS5060	500*600	60-600
EWC6060	600*600	60-600	EWS6060	600*600	60-600
EWC6080	600*800	60-1500	EWS6080	600*800	60-1500
EWC8080	800*800	100-1500	EWS8080	800*800	100-1500
Aluminum Die-Cast platform					
Stainless steel platter					
Model	Size(mm)	Cap.(kg)			
EWA3040	300*400	30-150			
EWA4252	420*520	60-300			

