

LMPPPOS

**Wireless Barcode Scanner
WBS-3**



32bit decode,5mil resolution
Can store 60thousand barcode
With the outstanding scanning speed
and decoding performance



With IP54 high performance protection
Unit functions normally after repeated
6.5 ft. (2 m) drops to concrete



Radio range: Up to 1000 ft. (300m)
direct line of sight in open air
Built-in rechargeable battery
Battery Charge time:fully charged (100%)
within 4 hours,can use 1week
Scan rate:150scan/sec



Decode&Scan engine

Indicator Light

Trigger(50million time)



"Beep,Beep"sound

Cradle



Decode all major 1D & below special barcode

GS1 Data Bar



GS1 Data Bar Limited



Barcode Edge Spot



Vague barcode



Long Barcode



abcdefghijklmnopqrstuvwxyz

Low Density Barcode



ABC1.0

Application:Factory,Logistics,Retail,Library management,Warehouse Check,Post and ect.



Website:www.lmppos.com
Phone:+86-15918668768
Contact:Colin

Email:sales@lmppos.com
Skype:lmppos

Wireless Barcode Scanner WBS-3



Features

32bit decode,5mil resolution

1 cradle can support 100 scanners

Radio range: Up to 1000 ft. (300m) direct line of sight in open air,typical indoor cordless range is 300 ft. (100m), but range will vary depending upon environment

The service life of the trigger is up to 50,000,000 times

Built-in rechargeable battery

Battery Charge time:fully charged (100%) within 4 hours,can use 1week

Inner Storage:1M bytes(can store 60,000pcs commodity code

Cover with rubber for well protection

Newly design ,fashionable and portable

Multi-interfaces just by changing cable

Perfect product for a wide variety of applications

Package



Performance Characteristics

Working Frequency Range 433MHz ISM

Light Source 650nm lazer

Depth of Field 1.8m

Scan rate 150 scan/sec

Sensor

Best resolution 5mil

Scanning Angle $\pm 60^\circ, \pm 65^\circ, \pm 42^\circ$ (right and left,back and forth,rotation)

Indicators Green/Red/Yellow LED&Beeper

Interface USB/PS2 keyboard/RS-232

Symbologies UPC-A,UPC-E,EAN-13,EAN-8,ISBN/ISSN,39 code, 39 code(ASCII),Cross 25 code, Industry 25 code, Matrix 25 code, Codabar, 128 code,93 code,11 code, cMSI/Plessey, UK/Plessey, UCC/EAN 128, GS1 DataBar ect

Electrical Characteristics

Power DC 5V \pm 0.25V

Current 25 mA(operation)-95mA, 250mA(Charge)

Lazer Lever National level 2 laser safety standards

Physical Characteristics

Inner Storage 1M bytes(can store 60,000pcs commodity code

Material ABS+PC/TPU(scanner),ABS+PC(cradle),PC(Led light)

Cradle

Support 100 scanners

Radio range Up to 1000 ft. (300m) direct line of sight in open air, Typical indoor cordless range is 300 ft. (100m), but range will vary depending upon environment

User Environment

Temperature 0°C to 45°C(operation), -40°C to 60°C(storage)

Humidity 5% to 90%

Sealing With IP54 high performance protection

Drop Unit functions normally after repeated 6.5 ft. (2 m) drops to concrete

Warranty++

The WBS-3 is warranted against defects in workmanship and materials for a period of 1 years (12 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions.